



IF IT'S SELLEYS IT WORKS™

Technical Data Sheet

Tradies Bog

Updated
04/06/12

DESCRIPTION

Tradies Bog is an easy to sand 2-part Polyester building filler for fast repairs to wood and most common building materials.

SIZES AVAILABLE

Tradies Bog is available in 550g, 900g & 1.6Kg tins. Cream in colour.

USES

Ideal for repairing window and door frames, architraves, skirting boards, sashes, timber, fibro, masonry, concrete, bricks, metal, alloy, fibre glass, tiles and ceramics.

TECHNICAL FEATURES

- Easy to sand.
- Excellent adhesion to a variety of surfaces.
- Sets hard in 20 minutes.
- Can be sawn, drilled, tapped, sanded and painted.
- Can be coloured with cement oxides or paint tinters (before adding hardener)

TECHNICAL DETAILS	
Appearance:	Resin: Cream paste.
	Hardener: Red paste.
Working Time:	3-8 minutes @ 25 °C
Set Time:	20 minutes @ 25 °C
Service Temp	-28 °C to +190 °C
Lap Shear Tensile Adhesion Strength (on steel):	8000 kPa
Chemical Resistance:	Resistant to fresh and salt water, acids, alkalis, oils
Shrinkage:	Negligible.

HOW TO USE

- Surface to be repaired should be clean, dry, unpainted and free from grease or oil.
- Stir Selleys Tradies Bog before use.
- Add 2.5cm length of hardener to every 16 cubic cm (heaped tablespoon) of Selleys Tradies Bog. Mix in hardener by working the Selleys Tradies Bog from side to side until thoroughly mixed. (If faster setting time is required, add more hardener).
- Apply with a putty knife slightly over filling to allow for sanding.
- It is easier to smooth off most of the excess with a Surform or Dreadnought file before it becomes rock hard. Ordinary files or sandpaper may be used once rock hard.
- Feather edges for a perfect finish. Clean tools with mineral turps, before product dries.
- Paint with water or oil based paint.
- Replace lid after use and store in a cool place.

LIMITATIONS

Selleys Tradies Bog will not adhere to polyethylene, polypropylene or Teflon®.

WARNINGS/FIRST AID & SHIPPING

INFORMATION: Refer to the **SDS** section located on the Selleys Website.



Ph: AU - 1300 555 205

Ph: NZ - 0800 735 539

Website - www.selleys.com.au

Email - selleys.customer.service@selleys.com.au

Head Office: 1 Gow Street, Padstow NSW 2211 AU

Page | 1

© 2010 Selleys Pty Limited
ABN 67 000 049 427

All information contained in this Product Information Sheet is as accurate and up-to-date as possible. Products can be expected to perform as indicated in this Sheet, so long as application procedures are followed as recommended. However, there are no expressed or implied warranties set out in this information other than those implied by Commonwealth, State or Territory Legislation.